

Hose ID	NPT	Camel No.	Amflo No.
---------	-----	-----------	-----------

Solid Brass Male Hose Barb Fittings

Select fitting to match hose inside diameter.

*All packages contain 10 fittings. Amflo part numbers with D suffix indicate display packs.

1/8"	1/8"	399
1/4"	1/8"	404
1/4"	1/4"	401
1/4"	1/4"	52-039
5/16"	1/4"	52-038
3/8"	1/4"	52-037
1/2"	1/4"	408
1/4"	3/8"	604
3/8"	3/8"	52-492
1/4"	3/8"-24	398
1/2"	3/8"	608
1/2"	1/2"	808
3/4"	3/4"	814

Hose O.D. Range	Clamp Width	Camel No.	Amflo No.
-----------------	-------------	-----------	-----------

Hose Clamps

Gear type clamps permit quick hose repair with simple tools. Stainless band, plated steel screw. 10 pack.

1/4" to 5/8"	5/16"	580
3/8" to 7/8"	5/16"	581



Hose Size	Camel No.	Amflo No.
-----------	-----------	-----------

Hose Splicer and Clamps Kits

Use to repair hose in-line repairs or install new hose end fittings.

3/8" Barb w/ clamp	411D
--------------------	------



Male Ball Swivels

Fitting may swivel and rotate without kinking or twisting of hose.

1/4"	1/4"	444S
3/8"	1/4"	446S

Male Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

1/4"	1/4"	401S
------	------	------

Hi-Volume Male Swivel Fittings

3/8"	1/4"	406S
------	------	------

Hose ID	NPT	Camel No.	Amflo No.
---------	-----	-----------	-----------

Solid Brass Female Fittings

1/4"	1/4"	441
3/8"	1/4"	461

Hose ID	NPT	Camel No.	Amflo No.
---------	-----	-----------	-----------

One Piece Female Swivel Fittings

Permits rotation of fitting without kinking or twisting of hose.

3/8"	1/4"	463
------	------	-----

Two Piece Swivel Female Fittings

1/4"	1/4"	442
5/16"	1/4"	452

Solid Brass Hose Splicers

1/4"	52-046	402
3/8"	52-044	602
1/2"		802

CAUTION: Fittings must be secured to hose with either hose clamps or crimped-on ferrules with a hose crimper. Hose barbs are intended for use on compressed air only with a maximum working pressure of 300 PSI.

Brass Hose Fittings

Lock-On Hose Barbs. Designed to use with Amflo's special lock-on hose. No ferrules or hose clamps are required. Not to be used with conventional hose. All lock-on packages contain 10 fittings unless otherwise marked.



401L



446SL



402L



366T



344X



3404



3403 RET



366R



344U



930



265

Hose ID *NPT Thread* *Amflo No.*

Lock-On Hose Barb Male

1/4"	1/4"	401L
3/8"	1/4"	406L

Lock-On Hose Barb Male Ball Swivel

3/8"	1/4"	446SL
------	------	-------

Lock-On Hose Barb Splicers

1/4"	402L
------	------

Female Crosses

Excellent for running several air lines from a common supply hose. Solid brass.

1/4" NPT	344X
3/8" NPT	366X

Female Tees

Run two lines from a common feed. Solid brass.

1/4" NPT	344T
3/8" NPT	366T

Three-Way Manifold

Strong machined aluminum construction. Each manifold accepts three outlet hoses or couplers. * 3404 and 3406 available in display packs.

1/4" NPTF	1/4" NPTF	3404*
3/8" NPTF	1/4" NPTF	3406*
1/2" NPTF	1/4" NPTF	3408

Flat Brass Construction.

3/8" NPTF	1/4" NPTF	3403RET
-----------	-----------	---------

Brass In-Line Swivels

1/4" male / female NPT	344R
3/8" male / female NPT	366R

Uniswivel

360° swivel action. 300 PSI.

1/4" NPTF x 1/4" NPTM	344U
-----------------------	------

Flow Passage *NPT* *Amflo No.*

Brass Drain Cocks

1/4"	1/4"	930
1/16"	1/8"	931

Flow Passage *NPT* *Amflo No.*

Tank Safety Valve

Safety valve is furnished with relief pressure preset.

1/4"	1/4" NPT (125 PSI)	265-RET
------	-----------------------	---------

Hose O.D.	Hose I.D.	NPT	Camel No.	Amflo No.
-----------	-----------	-----	-----------	-----------

Male Pipe Thread

1/2"	1/4"	1/4"	418
19/32"	1/4"	1/4"	419
5/8"	3/8"	1/4"	620
23/32"	3/8"	1/4"	623
21/32"	3/8"	3/8"	624
7/8"	1/2"	1/2"	828



Male NPT	Male NPT	Camel No.	Amflo No.
----------	----------	-----------	-----------

Male Pipe Couplings

Solid brass NPT.

1/8"	1/4"	324
1/4"	1/4"	344
3/8"	1/4"	346
3/8"	3/8"	366
1/2"	1/2"	388



Male NPT	Female NPT	Amflo No.
----------	------------	-----------

Bushings and Adaptors

Solid brass.

1/4"	1/8"	324F
1/8"	1/4"	342F
3/8"	1/4"	346F
1/2"	1/4"	348F
1/4"	3/8"	364F
1/2"	3/8"	368F



Pipe Coupling Female NPT

Solid brass.

1/4" x 1/4"	344F
-------------	------

344F



344F

CAUTION: Check hose O.D. and I.D. accurately before ordering. All packages contain 10 fittings.