

Hose Crimpers and Ferrules

855



Camel No. Amflo No. Size

Standard Hose Crimper

Provides production capabilities and "big tool" crimping advantages at a much lower cost. Heavy duty ductile iron castings and hardened steel dies provide long service life and positive crimping. Includes five dies for crimping 1/4" braid to 3/8" double braided hose.

55-001 855

Replacement Dies for Crimping Tools (above)

856-1	5/8"	(.6250)
856-2	37/64"	(.5781)
856-3	17/32"	(.5312)
856-4	31/64"	(.4844)
856-5	11/16"	(.6875)
856-7	7/16"	(.4375)
856-8	3/4"	(.7500)
856-9	13/16"	(.8175)
856-10	3/8"	(.3750)

Amflo No.

Lock-On Hose Assembly Tool

Simplifies the coupling of lock-on hose and fittings. Hose is placed in the self-tightening clamp while light pressure on the handle easily presses the special lock-on fitting into the hose. Adaptors for 1/4" and 3/8" fittings are included.

845



845

Amflo No. Ferrule I.D.

Brass Ferrules

Use with hose barb fittings. Make sure ferrule closely matches hose O.D. Use with hose crimpers on this page. Camel ferrules are 25 per box. Amflo ferrules are 50 per box.



7325-50



7329-50

7321-50	.478"
7322-50	.500"
7323-50	.527"
7325-50	.562"
7326-50	.593"
7327-50	.625"
7328-50	.656"
7329-50	.687"
7330-50	.718"
7331-50	.750"
7332-50	.781"
7333-50	.812"
7334-50	.825"
7335-50	.850"
3952-50	.875"
5029A-50	.900"
7242A-50	.937"

WARNING: The products on this page are designed for use on compressed air lines only. Select fitting to match hose diameter. Fittings must be secured with the proper size crimped-on ferrule. Do not exceed the pressure limitation of the hose and/or air operated devices being used. Failure to follow these directions exactly may cause fittings to separate from hose and may result in personal injury and/or property damage.