

Mist Coolant Unit and Accessories

40

Faucets - Features chrome plated bodies with brass internal parts and self adjusting u-cup packing. Handles are riveted and spouts are reinforced for long service life. Lever controlled operating valve. Oil resistant.

Amflo No.

Radiator Faucet

Aluminum spout. 1/4" NPTF inlet thread.

40

Radiator Faucet with Rubber Nozzle

Shock proof molded rubber nozzle protects painted finish. 1/4" NPTF. 60 PSI.

40R

Radiator Faucet with Rubber Nozzle. Shock proof molded rubber nozzle. Garden hose inlet thread.

41R

40R

Kink-it Radiator Filler

Lightweight easy to operate. Garden hose inlet thread. Press side of rubber tube to open valve.

43W

Mist Coolant Unit

For machine shop use in milling, drilling, grinding and for crankshaft turning equipment. Sets up in seconds, uses powerful compound magnet to hold it firm.

270A

Repair Parts:

270A-T 12" Spray Line Assembly. 1 each.

43W

Mist Coolant Concentrate

Specially formulated for all metals, including aluminum. Cools and lubricates, inhibits rust. Contains no nitrates. 1 gallon.

273-4

270A

273

Amflo No. 273

SPRAY COOLANT

NET CONTENTS 1 U.S. GALLON